



GENVIK
WE MAKE IT BETTER



WASTE WATER PUMPS



Applications :

- Hotels
- Houses
- Commercial Buildings
- Complexes
- Pumping Wastage water in Industries
- Tunnels
- Pumping Wastage water from Stock Farm
- Manhole Sewerage
- STP
- Pumping from Septic Tank.

Special Features :

- Dry Type High Efficiency motors.
- Equipped with an automatic reset motor protector.
- Heavy duty sealed bearings.
- In-Built lip seal to prevent ingress of slit and sand.

Performance Data :

S.N	Model	P1	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	1	2	3	4	5	
		kW	HP								0	1	2	3	4	5	
1	KGB-CV05-CT	0.5	0.6	400	-	2	2850	40	36	Head in M	0	3.6	7.2	10.8	14.4	18	
2	KGB-CV08-CM-AFA	0.8	1	230	16	4.8	2850	40	36		7.2	6.3	5.3	4.4			
3	KGB-CV08-CT-A	0.8	1	400	-	1.5	2850	40	36		12.1	9.9	8.4	7.3			

S.N	Model	P2	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	1	2	3	4	5
		kW	HP								0	1	2	3	4	5
1	KGB-CV12-DMs-AF	1.2	1.6	230	30	7.1	2850	50	40	Head in M	15.1	13.6	12.1	10.5	9	7.4
2	KGB-CV12-DT	1.2	1.6	400	-	3.1	2850	50	40		18.1	17	15.6	14	12.2	10.2

S.N	Model	P2	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	1	2	3	4	5
		kW	HP								0	1	2	3	4	5
1	KGB-CV26-ET	2.6	3.5	400	-	5.9	2850	65	45	Head in M	22	21.1	20.4	19.2	18.2	17
											0	3.6	7.2	10.8	14.4	18

S.N	Model	P2	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	2	4	6	8	10
		kW	HP								0	2	4	6	8	10
1	KGB-CV18-DT	1.85	2.5	400	-	4.4	2850	50	45	Head in M	18	16	13.8	11.5	9	6.5
2	KGB-CV26-DT	2.6	3.5	400	-	5.9	2850	50	45		20.9	19.6	17.5	15.2	13	10.5
3	KGB-CV30-DT	3	4	400	-	7.5	2850	50	45		22	21.8	20.5	18	15.3	12.3

S.N	Model	P2	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	2	4	6	8	10
		kW	HP								0	7	14	21.6	28.8	36
1	KGB-CV40-ET-A	4	5	400	-	9	2850	65	50	Head in M	19.1	18.5	17.9	17	15.6	14
											0	7 <td>14 <td>21.6 <td>28.8 <td>36 </td></td></td></td>	14 <td>21.6 <td>28.8 <td>36 </td></td></td>	21.6 <td>28.8 <td>36 </td></td>	28.8 <td>36 </td>	36

S.N	Model	P2	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	3	6	9	12	15
		kW	HP								0	10.8	21.6	32.4	43.2	54
1	KGB-CV55-FD-AA	5.5	7.5	400	-	12	2850	80	50	Head in M	29	27	24.6	21.6	18.5	15.8
											0	3 <td>6 <td>9 <td>12 <td>15 </td></td></td></td>	6 <td>9 <td>12 <td>15 </td></td></td>	9 <td>12 <td>15 </td></td>	12 <td>15 </td>	15

S.N	Model	P2	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	1	2	3	4	4.5
		kW	HP								0	4	7	10.8	14.4	16.2
1	KGT-CV07-CMs-AF	0.75	1	230	22	5.5	2850	40	6	Head in M	14.3	11.5	8.6	4.8		
2	KGT-CV07-CT	0.75	1	400	-	2.7	2850	40	6		14.3	11.5	8.6	4.8		
3	KGT-CV11-CMs-AF	1.1	1.5	230	30	7.5	2850	40	6		15.5	13.1	10	6.6		
4	KGT-CV11-CT-A	1.1	1.5	400	-	3.2	2850	40	7		15.5	13.1	10	6.6		

S.N	Model	P2	P2	Volt	µf	Amp	RPM	DL Size (In mm)	Solid (In mm)	l/sec m ³ /h	0	1	2	3	4	4.5
		kW	HP								0	4	7	10.8	14.4	16.2
1	KGT-CV18-CT	1.85	2.5	400	-	4.5	2850	40	7	Head in M	29	26	23	19.1	13	10
2	KGT-CV26-CT	2.6	3.5	400	-	5.8	2850	40	7		35	33	29	26.1	18.9	15